

Flame Tracker*

25 years trusted experience
with a half billion hours of
fired operation

Designed for peak performance and reliability

The Silicon Carbide (SiC) Flame Tracker dramatically improves gas turbine performance while significantly reducing maintenance requirements. Available for a variety of gas turbines, the Flame Tracker flame sensor's optical photodiode is designed for use with multiple fuels, low NOx combustors and steam injection. Reliable turbine operations for steam injection applications require the sensitivity provided by Flame Tracker.

Advantages

High sensitivity, fast response

Flame Tracker, with its SiC photodiode, has high sensitivity to the longer UV wavelengths that easily penetrate the fog of fuel and steam. This is advantageous over typical flame sensors that are sensitive to only the short UV wavelengths. In addition, the SiC sensor has an analog output with a very wide dynamic range and rapid response time. These features offer the ability to quickly—in less than 25 milliseconds—report flame status. This means interruption-free service and improved availability.

Reduced maintenance

The Flame Tracker flame sensor is equipped with quick disconnect connectors, allowing sensor replacement time to be reduced from hours to minutes. Its improved sensor-cooling feature lowers the impact of surrounding heat and extends the life of electronics.

Customized conversion kits

Customized flame sensor conversion kits are available for all turbine configurations. These sensor enhancements are mechanically and electrically interchangeable with existing systems. The kit solution simplifies upgrading older, maintenance-intensive systems to the superior performance of the Flame Tracker.



Multiple applications

Designed to replace existing sensors, the Flame Tracker is applicable to a variety of land-based and marine-based gas turbines, regardless of size. In addition, it is ETL, ATEX, and IECEx certified.

Reliable, low voltage operation

Providing a 4–20 mA industry-standard output signal, the Flame Tracker operates reliably with any fuel—with or without—steam injection. Unlike older flame sensors that require high voltage for operation, the Flame Tracker requires low voltage, which eliminates special wiring and explosion-proof conduit requirements.


Performance benefits

- Provides reliable operation when using any fuel
- Allows full operation during the water wash cycle
- Reduces maintenance time
- Operates on low voltage
- Provides rapid response to flameout
- Produces a wide dynamic range
- Customized conversion kits
- Meets all NFPA guidelines for flame detection on gas turbines
- Delivers 10 times the sensitivity of tube-style sensors

Specifications

Sensor responsivity and hydrocarbon flame emission spectrum

Spectral response



— Flame emission

— Geiger mueller

Sensitivity at shorter wavelengths is a poor match for the high intensity flame peak.

— SiC

Peak sensitivity closely matches the key flame peak at 310 nm.

Operating

Power requirements	24 VDC nominal, 12-30 VDC @ 100 mA
Output	4-20 mA (a module to convert output to other controller inputs is available)
Response time	< 25 milliseconds
Temperature range	-20°F to +300°F (-30°C to +150°C) ⁽ⁱ⁾ , 455°F (235°C) with specified water or air cooling
Process pressure	To 400 psig (2.8 MPa)
Sensitivity	5 mA @ 1×10^{10} photons/in ² /sec. @ 310 nm

(i) Thermal shutdown of the cool end occurs at $150 \pm 10^\circ\text{C}$

Material

Body mount	AISI 316 stainless steel
Housing	AISI 304 stainless steel (sealed and Argon filled)
Mechanical interface	3/4" NPT female
Electrical connector	MIL-C-38999 series III size 15 (5pin)
Sensor	Silicon Carbide (SiC) photodiode



industrial.ai

Copyright 2019 Baker Hughes Company. All rights reserved. Baker Hughes provides this information on an "as is" basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information.

GEA34179 (11/2019)

Baker Hughes 

bakerhughes.com